
Network layer

- * transport segment from sending to receiving host
- · on sending side encapsulates segments into datagrams
- * on reving side, delivers segments to transport layer
- network layer protocols in every host, router
- * router examines header fields in all IP datagrams passing through it



Two Key Network-Layer Functions

- * forwarding: move packets from router's input to appropriate router output
- * routing: determine route taken by packets from source to dest.
 - routing algorithms

analogy:

- * routing: process of planning trip from source to dest
- forwarding: process of getting through single interchange


Datagram Forwarding



Datagram Forwarding table

Destination Address Range	Link Interface
11001000 00010111 00010000 00000000 through 11001000 00010111 00010111 11111111	0
11001000 00010111 00011000 00000000 through	1
11001000 00010111 00011000 11111111	
11001000 00010111 00011001 00000000 through 11001000 00010111 00011111 11111111	2
otherwise	3

IP datagram format



IP Addressing: introduction


- * IP address: 32-bit identifier for host. router interface
- * interface: connection between host/router and physical link
 - router's typically have multiple interfaces
 - · host typically has one interface
 - IP addresses interface



associated with each 223.1.1.1 = 11011111 00000001 00000001 00000001 223

Subnets

- * IP address:
 - subnet part (high order bits)
 - host part (low order bits)
- What's a subnet ?
 - device interfaces with same subnet part of IP address
 - can physically reach each other without intervening router




.

Subnets

Recipe

- to determine the subnets, detach each interface from its host or router, creating islands of isolated networks
- each isolated network is called a subnet.



Subnet mask: /24

Maturagle Lavor 4

IP addressing: CIDR

CIDR: Classless InterDomain Routing

- subnet portion of address of arbitrary length
- address format: a.b.c.d/x, where x is # bits in subnet portion of address



Network Layer 4-9

IP addresses: how to get one?

Q: How does a host get IP address?

- * hard-coded by system admin in a file
 - Windows: control-panel->network->configuration->tcp/ip->properties
 - UNIX: /etc/rc.config
- DHCP: Dynamic Host Configuration Protocol: dynamically get address from as server
 - "plug-and-play"

Network Layer 4-10

IP addressing: the last word...

Q: How does an ISP get block of addresses?

- <u>A:</u> ICANN: Internet Corporation for Assigned Names and Numbers
 - allocates addresses
 - manages DNS
 - assigns domain names, resolves disputes

IPv6

- Initial motivation: 32-bit address space soon to be completely allocated.
- * Additional motivation:
 - header format helps speed processing/forwarding
 - header changes to facilitate QoS

IPv6 datagram format:

- fixed-length 40 byte header
- no fragmentation allowed

Network Layer 4-11 Network Layer 4-12

IPv6 Header (Cont)

Priority: identify priority among datagrams in flow Flow Label: identify datagrams in same "flow." (concept of "flow" not well defined).

Next header: identify upper layer protocol for data

ver	pri	flow label		
-	ayload	llen	next hdr	hop limit
source address (128 bits)				
destination address (128 bits)				
data				
4 32 bits — →				

Network Layer 4-1

Other Changes from IPv4


- Checksum: removed entirely to reduce processing time at each hop
- * Options: allowed, but outside of header, indicated by "Next Header" field
- * ICMPv6: new version of ICMP
 - additional message types, e.g. "Packet Too Big"
 - multicast group management functions

Network Laver 4-14

Transition From IPv4 To IPv6

- Not all routers can be upgraded simultaneous
 - no "flag days"
 - How will the network operate with mixed IPv4 and IPv6 routers?
- Tunneling: IPv6 carried as payload in IPv4 datagram among IPv4 routers


Tunneling Logical view: A B



Network Layer 4-15

Network Layer 4-16


Tunneling



Routingalgoritmer

Hur skapas innehållet i routingtabellerna??

Graph abstraction



Graph: G = (N,E)

 $N = set of routers = \{ u, v, w, x, y, z \}$


 $\mathsf{E} = \mathsf{set} \; \mathsf{of} \; \mathsf{links} \; = \! \{\; (\mathsf{u},\mathsf{v}), \; (\mathsf{u},\mathsf{x}), \; (\mathsf{v},\mathsf{x}), \; (\mathsf{v},\mathsf{w}), \; (\mathsf{x},\mathsf{w}), \; (\mathsf{x},\mathsf{y}), \; (\mathsf{w},\mathsf{y}), \; (\mathsf{w},\mathsf{z}), \; (\mathsf{y},\mathsf{z}) \; \}$

Remark: Graph abstraction is useful in other network contexts

Example: P2P, where N is set of peers and E is set of TCP connections

Network Layer 4-1

Graph abstraction: costs



- \cdot c(x,x') = cost of link (x,x')
- e.g., c(w,z) = 5
- cost could always be 1, or inversely related to bandwidth, or inversely related to congestion

Cost of path $(x_1, x_2, x_3, ..., x_p) = c(x_1, x_2) + c(x_2, x_3) + ... + c(x_{p-1}, x_p)$

Question: What's the least-cost path between u and z?

Routing algorithm: algorithm that finds least-cost path

Network Laver 4-20

Routing Algorithm classification

Global or decentralized information?

Global:

- all routers have complete topology, link cost info
- * "link state" algorithms

Decentralized:

- router knows physicallyconnected neighbors, link costs to neighbors
- iterative process of computation, exchange of info with neighbors
- "distance vector" algorithms

Static or dynamic?

Static:

 routes change slowly over time

Dynamic:

- routes change more quickly
 - periodic update
 - in response to link cost changes

Network Layer 4-21

A Link-State Routing Algorithm

Dijkstra's algorithm


- net topology, link costs known to all nodes
 - accomplished via "link state broadcast"
- all nodes have same info
 computes least cost paths
- computes least cost paths from one node ('source") to all other nodes
 - gives forwarding table for that node
- iterative: after k iterations, know least cost path to k dest.'s

Notation:

- C(X,y): link cost from node x to y; = ∞ if not direct neighbors
- D(v): current value of cost of path from source to dest. v
- p(v): predecessor node along path from source to v
- N': set of nodes whose least cost path definitively known

Network Layer 4-22

Dijsktra's Algorithm




Network Layer 4-23

Dijkstra's algorithm: example

Ste	o N'	D(v) p(v)	D(w) p(w)	D(x)	D(y) p(y)	D(z) p(z)
0	u	7,u	(3,u)	5,u	∞	
1	uw	6,w		(5,u	11,w	∞
2	uwx	6,w)		11,W	14,x
3	uwxv				(10,y)	14,x
4	uwxvy					(12,y)
5	uwxvyz					


Notes:

- construct shortest path tree by tracing predecessor nodes
- ties can exist (can be broken arbitrarily)



Dijkstra's algorithm: another example


S	tep	N'	D(v),p(v)	D(w),p(w)	D(x),p(x)	D(y),p(y)	D(z),p(z)
	0	u	2,u	5,u	1,u	∞	∞
	1	ux 🕶	2,u	4,x		2,x	∞
	2	uxy⊷	2,u	3,y			4,y
	3	uxyv		3,y			4,y
	4	uxyvw ←					4,y
	5	uxyvwz •					



Network Layer 4-2

Dijkstra's algorithm: example (2)

Resulting shortest-path tree from u:



Resulting forwarding table in u:

destination	link
v	(u,v)
×	(u,x)
У	(u,x)
w	(u,x)
z	(u,x)

Network Laver 4-26

Dijkstra's algorithm, discussion

Algorithm complexity: n nodes

- * each iteration: need to check all nodes, w, not in N
- n(n+1)/2 comparisons: O(n²)
- * more efficient implementations possible: O(nlogn)

Oscillations possible:

* e.g., link cost = amount of carried traffic









Network Layer 4-27

Distance Vector Algorithm

Bellman-Ford Equation (dynamic programming)

Define

 $d_x(y) := cost of least-cost path from x to y$


Then

$$d_{x}(y) = \min_{v} \{c(x,v) + d_{v}(y)\}$$

where min is taken over all neighbors v of x

Network Layer 4-28

Bellman-Ford example



Node that achieves minimum is next hop in shortest path → forwarding table

<u>Distance Vector Algorithm</u>

- * $D_x(y)$ = estimate of least cost from x to y
 - x maintains distance vector $\mathbf{D}_x = [\mathbf{D}_x(y): y \in \mathbb{N}]$
- node x:
 - knows cost to each neighbor v: c(x,v)
 - maintains its neighbors' distance vectors. For each neighbor v, x maintains $D_v = [D_v(y): y \in N]$

Network Layer 4-2

Distance vector algorithm (4)

Basic idea:

- from time-to-time, each node sends its own distance vector estimate to neighbors
- when x receives new DV estimate from neighbor, it updates its own DV using B-F equation:

 $D_x(y) \leftarrow min_x\{c(x,v) + D_y(y)\}$ for each node $y \in N$

 under minor, natural conditions, the estimate D_x(y) converge to the actual least cost d_x(y)

Network Layer 4-3

Distance Vector Algorithm (5)

Iterative, asynchronous: each local iteration caused

- by:local link cost change
- DV update message from neighbor


Distributed:


- each node notifies neighbors only when its DV changes
 - neighbors then notify their neighbors if necessary

Each node:



Network Layer 4-32





Distance Vector: link cost changes

Link cost changes:

- node detects local link cost change
- updates routing info, recalculates distance vector
- if DV changes, notify neighbors



 $t_{\it O}$: y detects link-cost change, updates its DV, informs its neighbors.

 $t_{\it J} \colon x$ receives update from y, updates its table, computes new least cost to x , sends its neighbors its DV.

 t_2 : y receives 2's update, updates its distance table. y's least costs do not change, so y does not send a message to z.

Network Layer 4-35

Distance Vector: link cost changes

Link cost changes:

- good news travels fast
- bad news travels slow -"count to infinity" problem!
- 44 iterations before algorithm stabilizes: see

Poisoned reverse:

- If Z routes through Y to get to X:
 - Z tells Y its (Z's) distance to X is infinite (so Y won't route to X via Z)
- will this completely solve count to infinity problem?



Comparison of LS and DV algorithms

Message complexity

- LS: with n nodes, E links, O(nE) msgs sent
- <u>DV:</u> exchange between neighbors only
 - convergence time varies

Speed of Convergence

- LS: O(n²) algorithm requires
 O(nE) msgs
 - may have oscillations
- * <u>DV</u>: convergence time varies
 - may be routing loops

 - count-to-infinity problem

Robustness: what happens if router malfunctions?

- node can advertise incorrect link cost
- each node computes only its own table

- DV node can advertise incorrect path cost
- each node's table used by others
 - error propagate thru network